

<b>Model</b>	<b>Recomm ended Working Load Per Mount (l b)</b>	<b>Base Footp rint LxW (in)</b>	<b>Base Bolt Center s (in)</b>	<b>Base Bolt DIA (in)</b>	<b>Base Thicknes s (in)</b>	<b>Stud DIA (in)</b>	<b>Min Free Height (in)</b>	<b>Overall Height (in)</b>	<b>Weight (lb)</b>
<a href="#"><u>M100-20S</u></a>	165-770	7.40 x 3.94	5.51	1/2	0.79	M20 (3/4" appro x)	4.09	6.77	4.0
<a href="#"><u>M100-24S</u></a>	165-770	7.40 x 3.94	5.51	1/2	0.79	M24 (1" appro x)	4.09	7.72	4.4
<a href="#"><u>M110-20S</u></a>	165-770	8.66 x 4.17	6.69	5/8	0.98	M20 (3/4" appro x)	4.80	7.48	4.4
<a href="#"><u>M110-24S</u></a>	165-770	8.66 x 4.17	6.69	5/8	0.98	M24 (1" appro x)	4.80	8.43	5.3
<a href="#"><u>M125H D-20S</u></a>	550-1650	9.45 x 5.00	6.69	5/8	0.98	M20 (3/4" appro x)	5.28	7.72	5.3
<a href="#"><u>M125H D-24S</u></a>	550-1650	9.45 x 5.00	6.69	5/8	0.98	M24 (1" appro x)	5.28	8.66	7.0
<a href="#"><u>M125XH D-24S</u></a>	1320-2200	9.45 x 5.00	6.69	5/8	0.98	M24 (1" appro x)	5.28	8.66	2.4
<a href="#"><u>M127H D-20S</u></a>	550-1650	9.45 x 5.00	7.17	5/8	0.98	M20 (3/4" appro x)	5.28	7.72	6.2
<a href="#"><u>M127H D-24S</u></a>	550-1650	9.45 x 5.00	7.17	5/8	0.98	M24 (1" appro x)	5.28	8.66	7.0
<a href="#"><u>M127XH D-24S</u></a>	1320-2200	9.45 x 5.00	7.17	5/8	0.98	M24 (1" appro x)	5.28	8.66	7.0

<b>Model</b>	<b>Recomm ended Working Load Per Mount (l b)</b>	<b>Base Footp rint LxW (in)</b>	<b>Base Bolt Center s (in)</b>	<b>Base Bolt DIA (in)</b>	<b>Base Thicknes s (in)</b>	<b>Stud DIA (in)</b>	<b>Min Free Height (in)</b>	<b>Overall Height (in)</b>	<b>Weight (lb)</b>
<a href="#"><u>M130H D-20S</u></a>	550-1650	9.45 x 5.00	7.17	5/8	0.98	M20 (3/4" appro x)	4.33	6.77	5.3
<a href="#"><u>M130H DLP- 20S</u></a>	550-1650	9.45 x 5.00	7.17	5/8	0.98	M20 (3/4" appro x)	3.39	6.77	5.7
<a href="#"><u>M130H D-24S</u></a>	550-1650	9.45 x 5.00	7.17	5/8	0.98	M24 (1" appro x)	4.33	7.72	6.4
<a href="#"><u>M130XH D-24S</u></a>	1320-2200	9.45 x 5.00	7.17	5/8	0.98	M24 (1" appro x)	4.33	7.72	6.4
<a href="#"><u>M130H DLP- 24S</u></a>	550-1650	9.45 x 5.00	7.17	5/8	0.98	M24 (1" appro x)	3.50	7.72	6.8
<a href="#"><u>M130XH DLP- 24S</u></a>	1320-2200	9.45 x 5.00	7.17	5/8	0.98	M24 (1" appro x)	3.50	7.72	6.8
<a href="#"><u>M136H D-24S</u></a>	1100-2640	9.45 x 5.71	7.17	5/8	0.98	M24 (1" appro x)	5.28	8.66	11.4
<a href="#"><u>M139H D-24S</u></a>	1100-2640	9.29 x 5.79	7.28 x 2.56	5/8	0.98	M24 (1" appro x)	4.88	8.27	11.9
<a href="#"><u>M140H D-24S</u></a>	1320-3520	9.45 x 5.59	7.17	5/8	0.98	M24 (1" appro x)	4.25	7.88	8.8
<a href="#"><u>M55- 12S</u></a>	55-440	5.28 x 2.95	4.00	3/8	0.57	M12 (1/2" appro x)	2.56	4.13	1.1

<b>Model</b>	<b>Recomm ended Working Load Per Mount (l b)</b>	<b>Base Footp rint LxW (in)</b>	<b>Base Bolt Center s (in)</b>	<b>Base Bolt DIA (in)</b>	<b>Base Thicknes s (in)</b>	<b>Stud DIA (in)</b>	<b>Min Free Height (in)</b>	<b>Overall Height (in)</b>	<b>Weight (lb)</b>
<a href="#"><u>M55-16S</u></a>	55-440	5.28 x 2.95	3.94 - 4.13	3/8	0.57	M16 (5/8" appro x)	2.68	5.00	1.3
<a href="#"><u>M75-16S</u></a>	165-660	6.97 x 3.86	5.00	1/2	0.79	M16 (5/8" appro x)	3.39	5.51	2.6
<a href="#"><u>M75-20S</u></a>	165-660	6.97 x 3.86	5.00	1/2	0.79	M20 (3/4" appro x)	3.62	6.30	2.9
<a href="#"><u>M85-16S</u></a>	165-660	7.48 x 3.86	5.51	1/2	0.79	M16 (5/8" appro x)	3.39	5.51	2.6
<a href="#"><u>M85-20S</u></a>	165-660	7.48 x 3.86	5.51	1/2	0.79	M20 (3/4" appro x)	3.62	6.30	2.9
<a href="#"><u>M90-20S</u></a>	165-770	6.97 x 3.94	5.00	1/2	0.79	M20 (3/4" appro x)	4.09	6.77	3.1
<a href="#"><u>M90-24S</u></a>	165-770	6.97 x 3.94	5.00	1/2	0.79	M24 (1" appro x)	4.09	7.72	3.5
<a href="#"><u>IFX95-20S</u></a>	110-770	6.97 x 3.94	5.00	1/2"	0.79	M20 (3/4" appro x)	4.17	7.01	4.0
<a href="#"><u>IFX95-24S</u></a>	110-770	6.97 x 3.94	5.00	1/2"	0.79	M24 (1" appro x)	4.17	7.95	4.4