

## PITTS CLUTCH MODELS AND BASIC SPECIFICATIONS

Series	Model	Qty/Box	Shipping		Static Torq (Lb Ft)	Voltage		Drive Type	Clutch Mount Brackets											
			Dims	Weight		12V	24V		Mount Style	Model	P/N	Mount Style	Model	P/N						
24	24D75-6	6	18 X 7 X 7	60	75	X	X	Belt	TYPE "A" / "B"											
AG	AG100	1	7 X 7 X 3	10	100	X	N/A	Belt	TYPE "B"											
		6	18 X 7 X 7	60																
	AG100L	1	7 X 7 X 3	10				X	Brake	TYPE "A"										
		6	18 X 7 X 7	60																
H24	H24D90	1	6 X 6 X 4	14	90	X	X	Shaft	SAE "A" 2 BOLT	B-H24-H27	13195									
		4	16 X 7 X 7	60																
	H24K90	1	6 X 6 X 4	14				N/A	Belt			SAE "A" 2 BOLT								
		4	16 X 7 X 7	60																
	H24V90	1	6 X 6 X 4	14				X	Belt			SAE "A" 2 BOLT								
		4	16 X 7 X 7	60																
H27	H27V150	1	6 X 6 X 4	16	150	X	X	Belt	SAE "A" 2 BOLT											
H28	H28D200	1	9 X 9 X 5	30	200	X	X	Shaft	SAE "B" 2-4	B-H28	13219									
	H28D200G	1							GRESEN											
	H28D300HT	1							SAE "B" 2-4											
	H28L200M	1	9 X 9 X 5	27	200	X	X	Brake	SPECIAL											
	H28V200	1						Belt	SAE "B" 2-4											
	H28V200G	1							GRESEN											
	H28V300HT	1							SAE "B" 2-4											
	H36	H36D400						1	14 X 14 X 10			54	400	X	X	Shaft	SAE "C" 2-4	B-H36-H49-C	13256	SAE "B" 2-4
H36D550HT		1	550																	
H44	H44D700	1	14 X 14 X 10	74	700	X	X	Shaft												
	H44D850HT	1							850											
H49	H49D1000	1	14 X 14 X 10	84	1,000	X	X	Shaft												
	H49D1200HT	1							1,200											
H55	H55D1500	1	14 X 14 X 10	135	1,500	X	X	Shaft	SAE "D" 2-4	B-H55	14219									
	H55D2000HT	1							2,000											

